

	Z 55i	Z 55	Z 45i	Z45	Z 35	X 50	X 40	X 30
Maximale buislengte (m)	55	55	45	45	35	55	45	35
Maximum vermogen (W)	1900	1900	1600	1600	1600	1900	1600	1300
Maximum lucht vermogen (W)	770	770	680	680	620	770	620	520
Volt (min-max) bij 50 Hz	207-244	207-244	207-244	207-244	207-244	207-244	207-244	207-244
Volume Lp Dp (A) + 2dp	64	64	64	64	64	64	64	64
Inhoud stofemmer	20	20	20	20	20	14	14	14
Terugslag klep	X	X	X	X	X	X	X	X
Geïntegreerd zuigcontact	X	X	X	X	X			
Standaard stofzak	X	X	X	X	X	X	X	X
Soft Start functie	X		X					
Afmetingen (mm - b x h)	345 x 780	345 x 780	345 x 780	345 x 780	345 x 780	375 x 575	375 x 575	375 x 575
Gewicht (kg)	9	8,5	9	8,5	8,5	7	7	7
Thermische beveiliging	X	X	X	X	X	X	X	X
Beveiliging overbelasting	X	X	X	X	X	X	X	X
Modbus RTU interface	X		X					
Verbinding met air handling unit	X	X	X	X	X	X	X	X